



THE RO/RO HYGIENIC ACOUSTIC Baffle SYSTEM

IAC Bulletin RoRo/1.02

A special system of cleanable, ceiling-mounted, retractable acoustic baffles, ideal for controlling noise and reducing reverberation in food production/processing and pharmaceutical facilities and other hygiene-sensitive areas

- Proven and Effective Sound Absorption
- Suitable for Wet and Dry Cleaning
- Bacteria-Resistant Finish
- Robust, Stainless Steel Construction
- Rapidly Installed and Fully Demountable

The IAC Ro/Ro Acoustic Baffle System has been specially designed to combat noise and reverberation problems inside buildings while being simple and quick to clean and maintain. Already highly popular in northern Europe, the system consists of demountable, sound absorbing, stainless steel framed panels (baffles), suspended from ceiling-mounted rails. The panels are arranged in rows with interconnecting wires which allow them to be installed/collected at one end for fast routine inspection and maintenance. All panels can be easily and swiftly removed (unclipped) from the mounting system for thorough cleaning elsewhere.

The standard size of the panels is 1200mm x 600mm x 80mm thick and two different non-porous finishes are available, each being suited to a particular cleaning method.

Please see overleaf for full product description and specification.

IDEAL FOR:

- Food Production Areas
- Meat and Fish Processing Plants
- Breweries and Bottling Plants
- Pharmaceutical and Medical Facilities
- Dairy and Confectionery Establishments

Any production environment where reverberation control and hygiene are of critical importance



IAC House, Moorside Road, WINCHESTER,
Hampshire, SO23 7US, United Kingdom.
Tel: +44 (0) 1962 873000 Fax: +44 (0) 1962 873111
E-mail: info@iacl.co.uk Website: www.iacl.co.uk

SPECIFICATION FOR THE IAC RO/RO SYSTEM

PANEL CONSTRUCTION, SIZE AND WEIGHT

Sound-absorbing Ro/Ro baffles are 1200mm long x 600mm wide x 80mm thick. Special (non-standard) panels can be made on request. Each baffle consists of a stainless steel frame inside which is a rigid, self-supporting mineral wool panel. Modules weigh between 6.5 and 8.5 kilograms, depending on the type of mineral wool panel used (see Panel Types, below).

PANEL TYPES

Type LP: Offers maximum sound absorption and is suitable for dry and “semi-wet” cleaning. Ideal for applications with low-to-moderate contamination levels, e.g. dairies, pharmaceutical plants etc.

Type CF: Offers a renewable plastic foil surface with good sound absorption for wet and dry cleaning. Suitable for moderate-to-high contamination levels, e.g. slaughter houses. Withstands daily wet cleaning. Plastic foil surface can be renewed at appropriate intervals.

ACOUSTIC PERFORMANCE


Type	Frequency (Hz)	125	250	500	1000	2000	4000
LP	Sabins/baffle	0.25	0.53	0.85	0.95	0.95	0.89
CF	Sabins/baffle	0.20	0.51	0.81	0.80	0.80	0.70

- The values quoted above are for a typical installation (with 900mm spaces between rows) and a full evaluation of site conditions must be carried out.
- Please refer to IAC for product selection.


Example of acoustic performance achieved:

A factory with a reflected ceiling area of 700m² had its *reverberent field* reduced by 6dB at 1000Hz using the unique IAC Ro-Ro Acoustic Baffle system.


INSTALLATION AND OPERATION




1. Baffles are mounted on a stainless steel rail and joined together using connecting wires.




2. Baffles are pushed to the far end of the rail.



3. Baffles are pulled along the full length of the rail until all connecting wires are taut.



4. Baffles can be removed, one by one, by ‘unclipping’ connecting wires.



IAC is a BS EN ISO 9001 quality registered company



United Kingdom

IAC House, Moorside Road,
WINCHESTER,
Hampshire, SO23 7US
Tel: +44 (0) 1962 873000
Fax: +44 (0) 1962 873111
E-mail: info@iac.co.uk
Website: www.iac.co.uk

Germany

Sohlweg 17,
D-41372 Niederkrüchten
Tel: (02163) 99910
Fax: (02163) 999123
E-mail: info@iac-gmbh.de
Website: www.iac-gmbh.de

Denmark

IAC Nordic A/S,
Jernholmen 44,
DK-2650 Hvidovre
Tel: +45 36 77 88 00
Fax: +45 36 77 50 88
E-mail: mail@iac-nordic.dk
Website: www.iac-nordic.dk

United States

1160 Commerce Avenue,
Bronx,
New York 10462-5599
Tel: (718) 931 8000
Fax: (718) 863 1138
E-mail: info@industrialacoustics.com
Website: www.industrialacoustics.com